

## AMENDMENTS TO THE CLAIMS

1. (CURRENTLY AMENDED) A bus comprising:

a master interface connectable to a master device external to said bus and configured to (i) receive an early command signal from said master device with an early timing relationship to  
5 a first clock edge of a system clock and (ii) present a bus wait signal to said master device ~~proximate a second clock edge of said system clock,~~ wherein said early timing relationship comprises validity both a set-up time before and a hold-time after a  
respective edge of said system clock;

10 a slave interface connectable to a slave device external to said bus and configured to (i) present a command signal to said slave device ~~a delay after~~ with a standard timing relationship to  
said first clock edge, ~~and~~ (ii) present said early command signal to said slave device with said early timing relationship to said  
15 first clock edge and (iii) receive a slave wait signal from said slave device, wherein said standard timing relationship comprises a delay after said respective clock edge; and

a control logic configured to (i) register said early command signal with said ~~system~~ first clock edge to generate said  
20 command signal, ~~and~~ (ii) multiplex said early command signal to said slave interface and (iii) multiplex ~~convert~~ said slave wait signal into said bus wait signal.

2. (CURRENTLY AMENDED) The bus according to claim 1, wherein (i) said master interface is further configured to receive an early address signal from said master device ~~before~~ with said early timing relationship to said first clock edge, (ii) said control logic is further configured to (a) multiplex said early address signal to said slave interface, (b) decode said early address signal to present an early device select signal and (c) register both said early address signal and said early device select signal with said ~~system~~ first clock edge to generate an address signal and a device select signal, respectively, and decode ~~said address signal to generate a device select signal,~~ and (iii) said slave interface is further configured to present (a) both said address signal and said device select signal to said slave device ~~said delay after~~ with said standard timing relationship to said first clock edge and (b) both said early address signal and said early device select signal to said slave device with said early timing relationship to said first clock edge.

3. (CURRENTLY AMENDED) The bus according to claim 2, wherein (i) said master interface is further configured to receive a no-address signal from said master device before said first clock edge and (ii) said control logic is further configured to inhibit

5     both said device select signal and said early device select signal  
in response to said no-address signal.

4.     (CURRENTLY AMENDED) The bus according to claim 1,  
wherein (i) said master interface is further configured to receive  
an early burst request signal from said master device ~~before~~ with  
said early timing relationship to said first clock edge, (ii) said  
5     control logic is further configured to (a) multiplex said early  
burst signal to said slave interface and (b) register said early  
burst request signal with said ~~system~~ first clock edge to generate  
a burst request signal, and (iii) said slave interface is further  
configured to present (a) said burst request signal to said slave  
10    device ~~said delay after~~ with said standard timing relationship to  
said first clock edge and (b) said early burst request signal to  
said slave device with said early timing relationship to said first  
clock edge.

5.     (PREVIOUSLY PRESENTED) The bus according to claim 1,  
wherein (i) said master interface is further configured to receive  
a bus request signal from said master device and present a bus  
grant signal to said master device, and (ii) said control logic is  
5     further configured to arbitrate in response to said bus request  
signal and generate said bus grant signal.

6. (CURRENTLY AMENDED) The bus according to claim 5, wherein said control logic is further configured to complete arbitration within one clock cycle of said system clock and present said command signal to said slave interface in a next clock cycle of said system clock.

7. (PREVIOUSLY PRESENTED) The bus according to claim 5, wherein (i) said master interface is further configured to receive a lock signal from said master device, and (ii) said control logic is further configured to halt arbitration responsive to said lock  
5 signal.

8. (CURRENTLY AMENDED) The bus according to claim 1, wherein said control logic comprises an address decoder configured to generate a plurality of early device select signals with said early timing relationship to said first clock edge responsive to an  
5 early address signal.

9. (CURRENTLY AMENDED) The bus according to claim 8, wherein said control logic further comprises a plurality of registers configured to register a plurality of early signals with said early timing relationship to said first clock edge ~~said system~~  
5 ~~clock, each of said early signals being valid before said first clock edge~~ to generate a plurality of standard signals ~~said delay~~

~~after~~ with said standard timing relationship to said first clock edge.

10. (ORIGINAL) The bus according to claim 9, wherein said control logic further comprises an arbitration logic configured to generate a bus grant signal.

11. (PREVIOUSLY PRESENTED) The bus according to claim 10, wherein said control logic further comprises a first multiplexer configured to multiplex said early signals from said master interface to said slave interface responsive to said bus grant signal.

12. (PREVIOUSLY PRESENTED) The bus according to claim 11, wherein said control logic further comprises a second multiplexer configured to multiplex a plurality of write data select signals from said master interface to said slave interface responsive to said bus grant signal.

13. (CURRENTLY AMENDED) A method for operating a bus connectable to a master device and a slave device both external to said bus, comprising the steps of:

(A) receiving an early command signal ~~before~~ with an early timing relationship to a first clock edge of a system clock

at a master interface of said bus from said master device, wherein  
said early timing relationship comprises validity both a set-up  
time before and a hold-time after a respective edge of said system  
clock;

10           (B) registering said early command signal with said  
~~system~~ first clock edge to generate a command signal;

          (C) presenting said command signal ~~a delay after~~ with a  
standard timing relationship to said first clock edge at a slave  
interface of said bus to said slave device, wherein said standard  
15 timing relationship comprises validity a delay after said  
respective clock edge;

          (D) multiplexing said early command signal to said slave  
interface;

~~(D)~~ (E) receiving a slave wait signal at said slave  
20 interface from said slave device;

~~(E)~~ converting (F) multiplexing said slave wait signal  
into a bus wait signal; and

~~(F)~~ (G) presenting said bus wait signal at said master  
interface to said master device ~~proximate a second clock edge of~~  
25 ~~said system clock.~~

14. (CURRENTLY AMENDED) The method according to claim  
13, further comprising the steps of:

receiving an early address signal ~~before~~ with said early timing relationship to said first clock edge at said master interface from said master device;

registering said early address signal in response to said first clock edge to generate an address signal;

presenting said address signal at said slave interface to said slave device ~~said delay after~~ with said standard timing relationship to said first clock edge;

presenting said early address signal at said slave interface with said early timing relationship to said first clock edge;

decoding said early address signal to generate ~~a~~ an early device select signal ~~in response to generating said address signal;~~  
and

presenting said early device select signal at said slave interface to said slave device ~~in response to decoding said address signal.~~

15. (CURRENTLY AMENDED) The method according to claim 14, further comprising the steps of:

receiving a no-address signal before said first clock edge at said master interface from said master device; and

inhibiting said early device select signal in response to receiving said no-address signal.

16. (CURRENTLY AMENDED) The method according to claim 13, further comprising the steps of:

receiving an early burst request signal ~~before~~ with said early timing relationship to said first clock edge at said master interface from said master device;

registering said early burst request signal with said system clock to generate a burst request signal in response to said first clock edge; ~~and~~

presenting said burst request signal at said slave interface to said slave device ~~said delay after~~ with said standard timing relationship to said first clock edge; ~~and~~

presenting said early burst request signal at said slave interface to said slave device with said early timing relationship to said first clock edge.

17. (PREVIOUSLY PRESENTED) The method according to claim 13, further comprising the steps of:

receiving a bus request signal at said master interface from said master device;

arbitrating in response to receiving said bus request signal; and

generating a bus grant signal at said master interface to said master device in response to arbitrating.



18. (CURRENTLY AMENDED) The method according to claim 17, wherein arbitrating is completed within one clock cycle of said system clock and said command signal is presented at said slave interface in a next clock cycle of said system clock.

19. (PREVIOUSLY PRESENTED) The method according to claim 17, further comprising the steps of:

receiving a lock signal at said master interface from said master device after; and

5 halting arbitration in response to receiving said lock signal.

20. (CURRENTLY AMENDED) A bus connectable to a master device and a slave device both external to said bus, comprising:

means for receiving an early command signal ~~before~~ with an early timing relationship to a first clock edge of a system clock at a master interface from said master device, wherein said early timing relationship comprises validity both a set-up time before and a hold-time after a respective edge of said system clock;

means for registering said early command signal with said ~~system~~ first clock edge to generate a command signal;

means for presenting said command signal ~~a delay after~~  
with a standard timing relationship to said first clock edge at a  
slave interface to said slave device, wherein said standard timing  
relationship comprises validity a delay after said respective clock  
15 edge;

means for receiving a slave wait signal at said slave  
interface from said slave device;

means for ~~converting~~ multiplexing said slave wait signal  
into a bus wait signal; and

20 means for presenting said bus wait signal at said master  
interface to said master device ~~proximate a second clock edge of~~  
~~said system clock.~~